

Application No. 10/666,165  
Amendment dated 22 December 2005  
Reply to Office Action dated 24 August 2005

Attorney Docket No. 5701-00297

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

Listing of Claims:

1. (currently amended): A magnetic sensor, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said magnetic circuit comprises at least a portion of said vehicle body or structure, said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, and said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure.

2. (currently amended): A magnetic sensor ~~as recited in claim 1~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said magnetic circuit comprises at least one ferromagnetic element of said vehicle body or structure, said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, and said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor; and

Application No. 10/666,165

Attorney Docket No. 5701-00297

Amendment dated 22 December 2005

Reply to Office Action dated 24 August 2005

10     b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure.

3. (currently amended): A magnetic sensor as recited in claim 1, wherein said at least one condition of said vehicle body or structure comprises a nominal condition of said vehicle body or structure.

4. (currently amended): A magnetic sensor as recited in claim 1, wherein said at least one condition of said vehicle body or structure comprises a deformed condition of said vehicle body or structure.

5. (currently amended): A magnetic sensor as recited in claim 1, wherein said at least one condition of said vehicle body or structure comprises a defective condition of said vehicle body or structure.

6. (currently amended): A magnetic sensor as recited in claim 1, wherein said at least one electrical circuit comprises a first electrical circuit comprising:

a. at least one first coil of said at least one coil;

b. at least one first capacitor in series with said at least one first coil; and

5     c. an oscillator, wherein said oscillator generates a first signal that is applied to said at least one first coil, and a first resonant frequency of said at least one first coil in combination with said at least one first capacitor is at or near a frequency of said first signal for at least one condition of said vehicle body or structure.

7. (original): A magnetic sensor as recited in claim 6, wherein said oscillator comprises a sinusoidal oscillator.

8. (original): A magnetic sensor as recited in claim 6, wherein said oscillator comprises a square wave oscillator.

Application No. 10/666,165

Attorney Docket No. 5701-00297

Amendment dated 22 December 2005

Reply to Office Action dated 24 August 2005

9. (original): A magnetic sensor as recited in claim 6, wherein said first electrical circuit is adapted so that said first signal applied to said at least one first coil is a mono-polar signal.

10. (currently amended): A magnetic sensor ~~as recited in claim 6~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor, and said at least one coil is adapted so as to incorporate an inherent capacitance of a magnitude sufficient to provide for filtering a harmonic component of said first signal; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure, and said at least one electrical circuit comprises a first electrical circuit comprising:

i) at least one first coil of said at least one coil;

ii) at least one first capacitor in series with said at least one first coil; and

iii) an oscillator, wherein said oscillator generates a first signal that is applied to said at least one first coil, and a first resonant frequency of said at least one first coil in combination with said at least one first capacitor is at or near a frequency of said first signal for at least one condition of said vehicle body or structure.

Application No. 10/666,165

Attorney Docket No. 5701-00297

Amendment dated 22 December 2005

Reply to Office Action dated 24 August 2005

11. (currently amended): A magnetic sensor ~~as recited in claim 6~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor, and a resistance of said at least one coil is greater than a total resistance of the remainder of elements of said at least one electrical circuit in series with said at least one coil and driven by said oscillator; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure, and said at least one electrical circuit comprises a first electrical circuit comprising:

i) at least one first coil of said at least one coil;

ii) at least one first capacitor in series with said at least one first coil; and

iii) an oscillator, wherein said oscillator generates a first signal that is applied to said at least one first coil, and a first resonant frequency of said at least one first coil in combination with said at least one first capacitor is at or near a frequency of said first signal for at least one condition of said vehicle body or structure.

12. (original): A magnetic sensor as recited in claim 6, wherein said at least one electrical circuit comprises at least one resistor in series with said at least one first coil.

Application No. 10/666,165

Amendment dated 22 December 2005

Attorney Docket No. 5701-00297

Reply to Office Action dated 24 August 2005

13. (currently amended): A magnetic sensor ~~as recited in claim 12~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, and said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure, said at least one electrical circuit comprises at least one resistor in series with said at least one first coil, a total resistance of said at least one resistor is less than a resistance of said at least one first coil and said at least one electrical circuit comprises a first electrical circuit comprising:

i) at least one first coil of said at least one coil;

ii) at least one first capacitor in series with said at least one first coil; and

iii) an oscillator, wherein said oscillator generates a first signal that is applied to said at least one first coil, and a first resonant frequency of said at least one first coil in combination with said at least one first capacitor is at or near a frequency of said first signal for at least one condition of said vehicle body or structure.

Application No. 10/666,165

Attorney Docket No. 5701-00297

Amendment dated 22 December 2005

Reply to Office Action dated 24 August 2005

14. (currently amended): A magnetic sensor ~~as recited in claim 6~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, and said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure, said electrical circuit is adapted for sensing at least one measure selected from a voltage across said at least one first coil, a current through said at least one first coil, a voltage across a resistor in series with said at least one first coil, and a voltage across said at least one first capacitor and said at least one electrical circuit comprises a first electrical circuit comprising:

i) at least one first coil of said at least one coil;

ii) at least one first capacitor in series with said at least one first coil; and

iii) an oscillator, wherein said oscillator generates a first signal that is applied to said at least one first coil, and a first resonant frequency of said at least one first coil in combination with said at least one first capacitor is at or near a frequency of said first signal for at least one condition of said vehicle body or structure.

15. (original): A magnetic sensor as recited in claim 6, further comprising a processor, a circuit, or a combination thereof adapted to determine at least one measure selected from a measure responsive to or related to an inductance of said at least one first coil, a measure responsive to or related to a resistance of said at least one first coil, a measure responsive to a phase angle between a voltage across said at least one first coil and a current through said at least one first coil, a measure of reactive power applied to said at least one first coil, and a measure of real power absorbed by said at least one first coil.

Application No. 10/666,165  
Amendment dated 22 December 2005  
Reply to Office Action dated 24 August 2005

Attorney Docket No. 5701-00297

16. (currently amended): A magnetic sensor ~~as recited in claim 6~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, and said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure, and said at least one electrical circuit comprises a first electrical circuit comprising:

i) at least one first coil of said at least one coil;

ii) at least one first capacitor in series with said at least one first coil, wherein said at least one first capacitor comprises first and second capacitors, and said at least one first coil is connected between said first and second capacitors, and said first and second capacitors and said at least one first coil are in series with one another; and

iii) an oscillator, wherein said oscillator generates a first signal that is applied to said at least one first coil, said oscillator is in series with said first and second capacitors said at least one first coil therebetween, and a first resonant frequency of said at least one first coil in combination with said at least one first capacitor is at or near a frequency of said first signal for at least one condition of said vehicle body or structure.

Application No. 10/666,165

Attorney Docket No. 5701-00297

Amendment dated 22 December 2005

Reply to Office Action dated 24 August 2005

17. (currently amended): A magnetic sensor ~~as recited in claim 1~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor, and said at least one coil comprises a first coil electrically connected to a first electrical circuit; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure, and said at least one electrical circuit comprises a second electrical circuit comprising:

a-i) at least one second coil of said at least one coil; and

b-ii) at least one second capacitor in parallel with said at least one second coil, wherein a second resonant frequency of said at least one second coil in combination with said at least one second capacitor is at or near an oscillation frequency of said time-varying magnetic flux coupled to said at least one second coil for at least one condition of said vehicle body or structure, and said first and second electrical circuits are electrically isolated from one another and magnetically coupled to one another.

18. (original): A magnetic sensor as recited in claim 17, wherein said second electrical circuit generates a second signal responsive to said time-varying magnetic flux coupled to said at least one second coil, and said second electrical circuit is adapted so that said second signal is mono-polar.



Application No. 10/666,165

Attorney Docket No. 5701-00297

Amendment dated 22 December 2005

Reply to Office Action dated 24 August 2005

19. (currently amended): A magnetic sensor ~~as recited in claim 6~~, comprising:

a. at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor, and said at least one coil comprises a first coil electrically connected to a first electrical circuit; and

b. at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure, said at least one electrical circuit comprises a first electrical circuit comprising:

i) at least one first coil of said at least one coil;

ii) at least one first capacitor in series with said at least one first coil; and

iii) an oscillator, wherein said oscillator generates a first signal that is applied to said at least one first coil, and a first resonant frequency of said at least one first coil in combination with said at least one first capacitor is at or near a frequency of said first signal for at least one condition of said vehicle body or structure, and said at least one electrical circuit comprises a second electrical circuit comprising:

e-iv) at least one second coil of said at least one coil; and

b-v) at least one second capacitor in parallel with said at least one second coil, wherein a second resonant frequency of said at least one second coil in combination with said at least one second capacitor is at or near an oscillation frequency of said time-varying magnetic flux coupled to said at least one second coil for at least one condition of said vehicle body or structure, said second resonant frequency is substantially equal or near to said frequency of said first signal for at least one condition of said vehicle body or structure, and said first and second electrical

Application No. 10/666,163  
Amendment dated 22 December 2005  
Reply to Office Action dated 24 August 2005

Attorney Docket No. 5701-00297

30                   circuits are electrically isolated from one another and magnetically coupled to one  
                    another.

20. (currently amended): A method of sensing a condition of a magnetic circuit, comprising:

a. operatively associating at least one coil with the magnetic circuit so that a time-varying  
magnetic flux in said magnetic circuit is magnetically coupled with said at least one  
coil, wherein said magnetic circuit comprises at least a portion of a vehicle body or  
5                   framestructure;

b. operatively coupling said at least one coil to at least one electrical circuit;

c. adapting said at least one electrical circuit so that an oscillation frequency of said time-  
varying magnetic flux is substantially at or near a resonant frequency of said at least  
one coil in cooperation with said at least one electrical circuit for at least one condition  
10                   of said magnetic circuit; and

d. sensing a condition of said magnetic circuit from a signal associated with said at least  
one electrical circuit responsive to said at least one coil.

21. (original): A method of sensing a condition of a magnetic circuit as recited in claim 20,  
wherein the operation of adapting said at least one electrical circuit comprises operatively  
coupling at least one first capacitor in series with at least one first coil of said at least one  
coil, and applying an oscillatory first signal in series with said at least one first coil.

22. (original): A method of sensing a condition of a magnetic circuit as recited in claim 21,  
wherein the operation of sensing a condition of said magnetic circuit comprises:

a. sensing a signal selected from a voltage across said at least one first coil, a current  
through said at least one first coil, a voltage across a resistor in series with said at least  
5                   one first coil, and a voltage across said at least one first capacitor, and

b. comparing said signal with a threshold.

23. (original): A method of sensing a condition of a magnetic circuit as recited in claim 22,  
further comprising sensing from said signal the operativeness of said electrical circuit  
including said at least one first coil.

**Application No. 10/666,165****Amendment dated 22 December 2005****Attorney Docket No. 5701-00297****Reply to Office Action dated 24 August 2005**

24. (original): A method of sensing a condition of a magnetic circuit as recited in claim 21, wherein the operation of sensing a condition of said magnetic circuit comprises:
- a. sensing a signal selected from a measure responsive to or related to an inductance of said at least one first coil, a measure responsive to or related to a resistance of said at least one first coil, a measure responsive to a phase angle between a voltage across said at least one first coil and a current through said at least one first coil, a measure of reactive power applied to said at least one first coil, and a measure of real power absorbed by said at least one first coil; and
  - b. comparing said signal with a threshold.
25. (previously presented): A method of sensing a condition of a magnetic circuit as recited in claim 24, further comprising sensing from said signal the operativeness of said electrical circuit including said at least one first coil.
26. (original): A method of sensing a condition of a magnetic circuit as recited in claim 21, wherein the operation of sensing a condition of said magnetic circuit comprises varying a frequency of said oscillatory first signal and sensing a response from said at least one electrical circuit responsive to said frequency.
27. (previously presented): A method of sensing a condition of a magnetic circuit as recited in claim 20, wherein said at least one electrical circuit comprises first and second electrical circuits and said at least one coil is electrically coupled to said first electrical circuit; the operation of adapting said at least one electrical circuit comprises electrically isolating said first and second electrical circuits from one another; magnetically coupling said first and second electrical circuits to one another; and operatively coupling at least one second capacitor in parallel with a second coil of said at least one coil so as to form a parallel circuit in said second electrical circuit; and the operation of sensing a condition of said magnetic circuit comprises sensing a voltage across said parallel circuit responsive to said time-varying magnetic flux in said magnetic circuit.

Application No. 10/666,165  
Amendment dated 22 December 2005  
Reply to Office Action dated 24 August 2005

Attorney Docket No. 5701-00297

28. (currently amended): A method of sensing a condition of a magnetic circuit as recited in claim 20, wherein said at least one coil is operatively associated with a vehicle body or structure, said magnetic circuit comprises a door of the vehicle, and said condition of said magnetic circuit comprises whether or not said door is latched.

29. (currently amended): A method of sensing a condition of a magnetic circuit as recited in claim 20, wherein said at least one coil is operatively associated with a vehicle body or structure, said magnetic circuit comprises a door of the vehicle, and said condition of said magnetic circuit comprises whether or not said door is involved in a crash, further comprising controlling the actuation of a safety restraint system responsive to sensing said condition that said door is involved in said crash.

30. (currently amended): A magnetic sensor ~~as recited in claim 1~~, further comprising:  
at least one coil operatively associated with a magnetic circuit of a vehicle body or structure, wherein said at least one coil is adapted to cooperate with a time-varying magnetic flux in said vehicle body or structure, said time-varying magnetic flux is generated or sensed by said at least one coil, and said time-varying magnetic flux is responsive to a condition of said vehicle body or structure that is sensed by the magnetic sensor;

at least one electrical circuit operatively coupled to said at least one coil, wherein said at least one electrical circuit is adapted so that said at least one coil in cooperation with said at least one electrical circuit exhibits a resonant or near-resonant condition in association with said time-varying magnetic flux for at least one condition of said vehicle body or structure; and

c. a processor, a circuit, or a combination thereof adapted to determine at least one measure selected from a measure responsive to or related to a resistance of said at least one first coil, a measure responsive to a phase angle between a voltage across said at least one first coil and a current through said at least one first coil, a measure of reactive power applied to said at least one first coil, and a measure of real power absorbed by said at least one first coil.

**Application No. 10/666,165**

**Amendment dated 22 December 2005**

**Reply to Office Action dated 24 August 2005**

**Attorney Docket No. 5701-00297**

**31. (previously presented): A method of sensing a condition of a magnetic circuit as recited in claim 20, wherein the operation of sensing a condition of said magnetic circuit comprises:**

- a. sensing a signal selected from a measure responsive to or related to a resistance of said at least one first coil, a measure responsive to a phase angle between a voltage across said at least one first coil and a current through said at least one first coil, a measure of reactive power applied to said at least one first coil, and a measure of real power absorbed by said at least one first coil; and**
- b. comparing said signal with a threshold.**